



AQUA TEC Series Peristaltic Pump is a reliable low cost solution, for light duty, chemical dosing applications.

Its compact size, and simple installation procedure (complete with wall mounting bracket) makes a versatile pump for installation which is also good in confined spaces. With IP65 rating, pump can be installed in outdoor applications. Available in fixed speed and (0/100%) adjustable speed versions.

Utilizing an innovative front cover design there are a number of advantages from the standard peristaltic pumps currently available on the market:

- Front cover is locked in position with hand knob.
- When front cover is removed squeeze tube can be easily removed by hand.
- Good structural strength as the rotor drive shaft is supported both above and below the rotor.

TECHNICAL FEATURES:

- Self Priming
- ON/OFF Switch
- Fixed or Adjustable Speed Models
- Santoprene or Silicon Squeeze Tube
- Power Supply 230VAC / 24VDC on request
- IP65 Protection
- Dimension 91 x 129 x 104mm
- Optional Level Input (interlock)
- Optional Quick Disconnect Power Plug

Model	Type	Flow (l/hr)	Pressure (bar)	Voltage	Tube
TEC-RS 1.5.01	Fixed Speed	1.5	1	230VAC	Santoprene
TEC-RS 03.01	Fixed Speed	3	1	230VAC	Santoprene
TEC-RS 04.01	Fixed Speed	4	1	230VAC	Santoprene
TEC-RS 06.01	Fixed Speed	6	1	230VAC	Santoprene
TEC-RS 01.03	Fixed Speed	1	3	230VAC	Santoprene
TEC-R 1.5.03	Adjustable Speed	1.5	3	230VAC	Santoprene
TEC-R 04.01	Adjustable Speed	4	1	230VAC	Santoprene
TEC-R 06.01	Adjustable Speed	6	1	230VAC	Santoprene
TEC-R 13.01	Adjustable Speed	13	0	230VAC	Santoprene

STANDARD INSTALLATION KIT (water treatment)



PP Weighted Foot Filter
 Viton Lip Check Valve
 c/w Tube Connection



PP Injection Nozzle
 Viton Squeeze Valve
 c/w Tube Connection



Wall Mounting Bracket
 c/w Screws & Plugs



2m Roll PVC Tube
 2m Roll PE Tube

Optional



Quick Disconnect
 Power Supply

